



National Transmission Corporation

28 June 2021

SUPPLEMENTAL/BID BULLETIN ADDENDUM NO. 1

SUBJECT : **SUPPLY AND DELIVERY OF AUDIO-VISUAL (AV) SYSTEM WITH INSTALLATION, CONFIGURATION, SET UP, COMMISSIONING AND TESTING.** *Reference No. PB210601-EA30 / PR No. CISIT-21-97272*

TO ALL CONCERNED:

Please be informed of the following amendments on the Bidding Document and for the purchase or payment for the Bidding Document.

ISSUES	AGREEMENTS											
<p>1. Technical Specifications</p> <p>A. Multi-Purpose Room</p> <ul style="list-style-type: none"> • Item A.1 • Item A.3 • HDMI Matrix Switcher <p>B. Boardroom</p> <ul style="list-style-type: none"> • item B.1 	<table border="1" style="width: 100%;"> <thead> <tr> <th style="text-align: center;"><i>From</i></th> <th style="text-align: center;"><i>To</i></th> </tr> </thead> <tbody> <tr> <td data-bbox="544 796 1059 1124"> 49" LCD Videowall Panel, 3.5mm bezel to bezel, 500nits, Visual Angle: Horizontal:178°, Vertical:178°(CR≥10), Resolution 1920x1080, ColourType:Colour/Monochrome, Video Input Connectors: VGA×1, DVI×1, BNC×1, YPbPr×1, HDMI×1, Dimensions mm: 1078 x 608 x 114 </td> <td data-bbox="1070 796 1530 1124"> 49" LCD Videowall Panel, 3.5mm bezel to bezel, 500nits, Visual Angle: Horizontal:178°, Vertical:178°(CR≥10), Resolution 1920x1080, Video Input Connectors: DVI×1, HDMI×1, </td> </tr> <tr> <td data-bbox="544 1124 1059 1596"> PTZ Camera 20x topical Zoom White, High-quality glass lens and 54.7° horizontal angle view, picture is clear under low illumination (0.5 lux @ F1.8) conditions, Video Systems: 1920x1080 / 1280x720. p60/50/30/25/59.94/29.97,1920x1080 i60/50/59.94, Shutter Auto and Manual, White Balance: Auto, Manual, One Push, 3000K-7000K, 255 supported number of presets, embeds audio on HDMI and SDI, Ports: RJ45, USB, VISCA3.5mm, Apperture: F1.6-F1,Focal Length:4.9-98 mm </td> <td data-bbox="1070 1124 1530 1596"> PTZ Camera 20x Zoom, white with 54.7 degrees Horizontal field of view, : High SNR CMOS combined with digital noise reduction,Full HD 1080p60,Video Output: 3G-SDI, HDMI up to 1080p60 and USB 2.0 up to 1080p30 </td> </tr> <tr> <td data-bbox="544 1596 1059 1775"> ➤ The HDMI Matrix Switcher is also required on the Multi-purpose specification. Using the technical specifications in Item B.8 on the Bidding Documents. </td> <td data-bbox="1070 1596 1530 1775"></td> </tr> <tr> <td data-bbox="544 1775 1059 2063"> 86" SMART TV, 3840x2160 resolution,4k upscale, Speaker Output 20 watts, Bluetooth V.5, surround ready, Wi-Fi ready, wide viewing angle, TruMotion/ Refresh rate: 60FPS/TM120, with Filmmaker mode features, 4 HDMI input (2 rear/2 side), 3 USB port (2 rear/1 side), Component Connectivity, 1 RF IN. </td> <td data-bbox="1070 1775 1530 2063"> 86" SMART TV, 3840x2160 resolution,4k upscale, Speaker Output 20 watts, Bluetooth V.5, surround ready, Wi-Fi ready, wide viewing angle, 3 HDMI input,2 USB port, 1 RF IN. </td> </tr> </tbody> </table>	<i>From</i>	<i>To</i>	49" LCD Videowall Panel, 3.5mm bezel to bezel, 500nits, Visual Angle: Horizontal:178°, Vertical:178°(CR≥10), Resolution 1920x1080, ColourType:Colour/Monochrome, Video Input Connectors: VGA×1, DVI×1, BNC×1, YPbPr×1, HDMI×1, Dimensions mm: 1078 x 608 x 114	49" LCD Videowall Panel, 3.5mm bezel to bezel, 500nits, Visual Angle: Horizontal:178°, Vertical:178°(CR≥10), Resolution 1920x1080, Video Input Connectors: DVI×1, HDMI×1,	PTZ Camera 20x topical Zoom White, High-quality glass lens and 54.7° horizontal angle view, picture is clear under low illumination (0.5 lux @ F1.8) conditions, Video Systems: 1920x1080 / 1280x720. p60/50/30/25/59.94/29.97,1920x1080 i60/50/59.94, Shutter Auto and Manual, White Balance: Auto, Manual, One Push, 3000K-7000K, 255 supported number of presets, embeds audio on HDMI and SDI, Ports: RJ45, USB, VISCA3.5mm, Apperture: F1.6-F1,Focal Length:4.9-98 mm	PTZ Camera 20x Zoom, white with 54.7 degrees Horizontal field of view, : High SNR CMOS combined with digital noise reduction,Full HD 1080p60,Video Output: 3G-SDI, HDMI up to 1080p60 and USB 2.0 up to 1080p30	➤ The HDMI Matrix Switcher is also required on the Multi-purpose specification. Using the technical specifications in Item B.8 on the Bidding Documents.		86" SMART TV, 3840x2160 resolution,4k upscale, Speaker Output 20 watts, Bluetooth V.5, surround ready, Wi-Fi ready, wide viewing angle, TruMotion/ Refresh rate: 60FPS/TM120, with Filmmaker mode features, 4 HDMI input (2 rear/2 side), 3 USB port (2 rear/1 side), Component Connectivity, 1 RF IN.	86" SMART TV, 3840x2160 resolution,4k upscale, Speaker Output 20 watts, Bluetooth V.5, surround ready, Wi-Fi ready, wide viewing angle, 3 HDMI input,2 USB port, 1 RF IN.	
<i>From</i>	<i>To</i>											
49" LCD Videowall Panel, 3.5mm bezel to bezel, 500nits, Visual Angle: Horizontal:178°, Vertical:178°(CR≥10), Resolution 1920x1080, ColourType:Colour/Monochrome, Video Input Connectors: VGA×1, DVI×1, BNC×1, YPbPr×1, HDMI×1, Dimensions mm: 1078 x 608 x 114	49" LCD Videowall Panel, 3.5mm bezel to bezel, 500nits, Visual Angle: Horizontal:178°, Vertical:178°(CR≥10), Resolution 1920x1080, Video Input Connectors: DVI×1, HDMI×1,											
PTZ Camera 20x topical Zoom White, High-quality glass lens and 54.7° horizontal angle view, picture is clear under low illumination (0.5 lux @ F1.8) conditions, Video Systems: 1920x1080 / 1280x720. p60/50/30/25/59.94/29.97,1920x1080 i60/50/59.94, Shutter Auto and Manual, White Balance: Auto, Manual, One Push, 3000K-7000K, 255 supported number of presets, embeds audio on HDMI and SDI, Ports: RJ45, USB, VISCA3.5mm, Apperture: F1.6-F1,Focal Length:4.9-98 mm	PTZ Camera 20x Zoom, white with 54.7 degrees Horizontal field of view, : High SNR CMOS combined with digital noise reduction,Full HD 1080p60,Video Output: 3G-SDI, HDMI up to 1080p60 and USB 2.0 up to 1080p30											
➤ The HDMI Matrix Switcher is also required on the Multi-purpose specification. Using the technical specifications in Item B.8 on the Bidding Documents.												
86" SMART TV, 3840x2160 resolution,4k upscale, Speaker Output 20 watts, Bluetooth V.5, surround ready, Wi-Fi ready, wide viewing angle, TruMotion/ Refresh rate: 60FPS/TM120, with Filmmaker mode features, 4 HDMI input (2 rear/2 side), 3 USB port (2 rear/1 side), Component Connectivity, 1 RF IN.	86" SMART TV, 3840x2160 resolution,4k upscale, Speaker Output 20 watts, Bluetooth V.5, surround ready, Wi-Fi ready, wide viewing angle, 3 HDMI input,2 USB port, 1 RF IN.											